Pendaflex
FROM TO DO... TO DONE

Pendaflex
FROM TO DO... TO DONE

Pendaflex
FROM TO DO... TO DONE

6527

NATIONAL BUREAU OF STANDARDS REPORT

6527

MEASUREMENTS OF THE THERMAL CONDUCTIVITY OF SEVERAL EXPLOSIVES BY THE CONDUCTIVE DISC METHOD

BY

H. E. Robinson, D. R. Flynn, and T. W. Watson

Report to the
Fire Protection Section
Building Technology Division
NBS

U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

THE NATIONAL BUREAU OF STANDARDS

Functions and Activities

The functions of the National Bureau of Standards are set forth in the Act of Congress, March 3, 1901, as amended by Congress in Public Law 619, 1950. These include the development and maintenance of the national standards of measurement and the provision of means and methods for making measurements consistent with these standards; the determination of physical constants and properties of materials; the development of methods and instruments for testing materials, devices, and structures; advisory services to Government Agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; and the development of standard practices, codes, and specifications. The work includes basic and applied research, development, engineering, instrumentation, testing, evaluation, calibration services, and various consultation and information services. A major portion of the Bureau's work is performed for other Government Agencies, particularly the Department of Defense and the Atomic Energy Commission. The scope of activities is suggested by the listing of divisions and sections on the inside of the back cover.

Reports and Publications

The results of the Bureau's work take the form of either actual equipment and devices or published papers and reports. Reports are issued to the sponsoring agency of a particular project or program. Published papers appear either in the Bureau's own series of publications or in the journals of professional and scientific societies. The Bureau itself publishes three monthly periodicals, available from the Government Printing Office: The Journal of Research, which presents complete papers reporting technical investigations; the Technical News Bulletin, which presents summary and preliminary reports on work in progress; and Basic Radio Propagation Predictions, which provides data for determining the best frequencies to use for radio communications throughout the world. There are also five series of nonperiodical publications: The Applied Mathematics Series, Circulars, Handbooks, Building Materials and Structures Reports, and Miscellaneous Publications.

Information on the Bureau's publications can be found in NBS Circular 460, Publications of the National Bureau of Standards ($1.25) and its Supplement ($0.75), available from the Superintendent of Documents, Government Printing Office, Washington 25, D. C.

Inquiries regarding the Bureau's reports should be addressed to the Office of Technical Information, National Bureau of Standards, Washington 25, D. C.

NATIONAL BUREAU OF STANDARDS REPORT

NBS PROJECT
1002-12-4822

September 1, 1959

NBS REPORT
6527

Measurements of the Thermal Conductivity of Several Explosives by the Conductive Disc Method

by

H. E. Robinson, D. R. Flynn, and T. W. Watson
Heat Transfer Section
Building Technology Division

Report to the
Fire Protection Section
Building Technology Division
NBS

IMPORTANT NOTICE

NATIONAL BUREAU OF S
intended for use within the
to additional evaluation and
listing of this Report, either
the Office of the Director, N
however, by the Governmen
to reproduce additional cop

progress accounting documents
rmally published it is subjected
reproduction, or open-literature
ssion is obtained in writing from
Such permission is not needed,
prepared if that agency wishes

Approved for public release by the Director of the National Institute of Standards and Technology (NIST) on October 9, 2015.

U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

Measurements of the Thermal Conductivity of Several Explosives by the Conductive Disc Method

by

H. E. Robinson, D. R. Flynn and T. W. Watson

1. INTRODUCTION

In connection with determinations of the thermal properties of explosives and solid propellants, undertaken by the Fire Protection Section of the National Bureau of Standards for the Naval Ordnance Laboratory, measurements were desired of the thermal conductivity of these materials. Because of possible danger of ignition of the materials, it was decided that the tests should be made on samples of limited size (less than 1 lb) in an available small underground vault, with controls and observations at a station outside the vault.

The Heat Transfer Section was consulted concerning the possibility of providing a suitable reliable apparatus for making these thermal conductivity measurements. A new type of thermal conductivity measuring apparatus, which had been under mathematical consideration, appeared more promising for this application than several alternative methods that were considered. Accordingly, the Heat Transfer Section constructed an appropriate apparatus of the new type, the design and calibration of which are described below.

2. DESCRIPTION

The essential elements of the "conductive disc" apparatus consist of a circular disc of metal sandwiched between two specimens of the same diameter, which in turn are sandwiched between two water-cooled plates of the same diameter (see Figure 1). The conductive disc is uniformly heated at its circular edge by means of electrical resistance wire set in a groove. The heat generated at the disc edge tends to flow in the disc radially toward its center, and also to flow from the disc through the two specimens to the uniform-temperature cold plates. Thus, the steady-state temperature of the conductive disc decreases toward its center. By measuring the temperature of the disc at its center and at a

Measurements of the Thermal Conductivity of Several Explosives by the Conducting Disc Method

by

R. S. Robinson, D. B. Flynn and T. W. Watson

1. INTRODUCTION

In connection with determinations of the thermal properties of explosives and solid propellants, undertaken by the Fire Protection Section of the National Bureau of Standards for the Naval Ordnance Laboratory, measurements were desired of the thermal conductivity of these materials. Because of possible danger of ignition of the materials, it was decided that the tests should be made on samples of limited size (less than 1 lb) in an available small underground vault, with controls and observations at a station outside the vault.

The Heat Transfer Section was consulted concerning the possibility of providing a suitable reliable apparatus for making these thermal conductivity measurements. A new type of thermal conductivity measuring apparatus, which had been under mathematical consideration, appeared more promising for this application than several alternative methods that were considered. Accordingly, the Heat Transfer Section constructed an appropriate apparatus of the new type, the design and calibration of which are described below.

2. DESCRIPTION

The essential elements of the "conducting disc" apparatus consist of a circular disc of metal sandwiched between two specimens of the same diameter, which in turn are sandwiched between two water-cooled plates of the same diameter (see Figure 1). The conducting disc is uniformly heated at its circular edge by means of electrical resistance wire set in a groove. The heat generated at the disc edge tends to flow in the disc radially toward its center, and also to flow from the disc through the two specimens to the uniform-temperature cold plates. Thus, the steady-state temperature of the conducting disc decreases toward its center. By measuring the temperature of the disc at its center and at a

suitable radius, the effective conductance of the specimens can be calculated, if the temperature of the cold plates and the conductivity and thickness of the disc metal are known.

The apparatus constructed has a 6-inch diameter disc of Type 303 stainless steel, fine-ground to a uniform thickness of 0.7264 cm. In addition to one thermocouple at the center, three additional thermocouple junctions are located at 120° angular spacing at a radius of 5.080 cm, all thermocouple junctions being inset in metallic contact with the stainless steel at one surface of the disc. The cold plates are 6-inch discs of brass, 1 cm thick, with several turns of 3/8-inch copper tube soldered to their non-working sides for circulation of coolant. The working surfaces of the cold plates were turned flat in a lathe after the soldering was completed. A thermocouple junction is inset in the brass disc at its center for measuring its temperature. The dimensions selected for the conductive disc of the apparatus were predicated on measurements on specimens 1/2 inch thick by 6 inches in diameter, having thermal conductivities in the range from 0.5 to 5.0 mw/cm C.

The heater winding in the edge-groove of the conductive disc consists of approximately 13 ft of No. 30 constantan wire, bifilarly wound, insulated with alundum-saturated fiberglass sleeving. Its electrical resistance is approximately 60 ohms.

Associated equipment includes a 20 gal. tank with a laboratory immersion pump for circulating water through the cold plate coils at about 1 gpm, a voltage regulator and a variable a-c transformer for power supply to the disc heater, and a precision potentiometer for thermocouple readings. All thermocouples are made of No. 30 copper and constantan wires, and are used with the reference junctions at 0°C.

3. USE AND ELEMENTARY ANALYSIS OF THE APPARATUS

An approximate analysis of the conductive disc method is given below, adequate for showing its chief operating characteristics, for designing the apparatus for the measurements desired, and for enabling certain computations of the test results.

A more rigorous analysis of the method is being made to develop a comprehensive mathematical treatment of the conductive disc apparatus, but is not needed for the apparatus

described here. As used in the tests reported here, the apparatus was calibrated by means of a guarded hot plate thermal conductivity apparatus. The calibration curve thus established served as a means for translating the measurements made in the disc apparatus into conductivity determinations tantamount to those that would have been obtained in tests in the guarded hot plate.

For steady temperature conditions, an approximate differential equation for the disc apparatus (which neglects non-radial temperature gradients in the disc, and radial temperature gradients in the specimens) is

$$2\pi r m K \left(\frac{d^2v}{dr^2} + \frac{1}{r}\frac{dv}{dr}\right)dr - 2\pi r dr v\left(\frac{K}{L} + \frac{k'}{L'}\right) = 0 \qquad (1)$$

in which the first part represents the change in radially-directed heat flux in the disc in a radial distance dr at a radius r, and the second part represents the flow of heat from the disc toward the cold plates through both specimens, through the disc surface area between r and (r+dr). In equation (1), m is the thickness of the conductive disc, K is its thermal conductivity, k and k' are the thermal conductivities of the two specimens and L and L' their thicknesses, and v is the temperature of the disc surface referred to the cold plate temperature as 0. It is assumed in equation (1) that the conductivities of the disc and specimens are constant at values corresponding to their mean temperatures.

Equation (1) becomes, upon simplification,

$$\frac{d^2v}{dr^2} + \frac{1}{r}\frac{dv}{dr} - \mu^2 v = 0 \qquad (2)$$

where

$$\mu^2 = \frac{1}{mK}\left(\frac{K}{L} + \frac{k'}{L'}\right) \qquad (2a)$$

Equation (2) is Bessel's equation of order zero, having the solution

$$v = AI_0(\mu r) \qquad (3)$$

Since $I_0(0) = 1$,

$$\frac{V}{V_0} = I_0(\mu R) \qquad (4)$$

where V_0 is the temperature of the disc surface at radius 0, and V the disc surface temperature at radius R, and where I_0

is the modified Bessel's function of the first kind and of order 0.a/

The mean temperature of the disc within the radius R, referred to the observed temperature of the cold plates as zero, is given by

$$V = \frac{1}{\pi R^2} \int_0^R 2\pi r V_0 I_0(\mu r) dr = \frac{2V_0 I_1(\mu R)}{\mu R} \qquad (5)$$

where I_1 is the modified Bessel's function of the first kind, of order 1. It is found, using tables of I_1, that

$$\frac{2V_0 I_1(\mu R)}{\mu R} = \frac{V_0 + V}{2} \quad \text{to within } 1/2\% \text{ for } V/V_0 < 1.4.$$

Thus for the tests reported, wherein $V/V_0 < 1.3$, it is adequate to take the actual mean temperature of the disc in a test as

$$t_d = 0.5(V_0 + V) + t_c \qquad (6)$$

where t_c is the observed temperature of the cold plates.

Similarly, the mean temperature of the specimen in a test is calculated as

$$t_s = 0.5(t_d + t_c) = 0.25(V_0 + V) + t_c \qquad (7)$$

4. CALIBRATION

If the value of kt were known accurately, equations (4) and (5) would serve to determine $(x/L + x'/L')$, within the limit of exactness of the I_0 solution. However, it was not feasible to obtain a piece of the metal used for the disc, of size adequate for a direct measurement of its thermal conductivity, k.

Further, it was desired to use in a test only one specimen of explosive, rather than two, and therefore a permanent "dummy specimen" was used in all tests in place of a duplicate of the principal specimen. This consisted of a 6-inch diameter disc of 1-inch thick semi-rigid glass-fiber

---

a/ Values of $I_0(x)$ and $I_1(x)$ are available to 5 places in tabulated form for values of x from 0 to 3 in increments of 0.001 (Tablitsy znacheniĭ funktsiĭ Besselia ot mnimogo argumenta, ... 1950, Moscow).

insulating board of stable low thermal conductivity (0.340 mw/cm C at 30°C) maintained at a constant thickness of 0.491 inch during use by three small fiber pegs thrust perpendicularly through the board. The lower cold plate of the apparatus, the dummy specimen, and the conductive disc were fastened together with rubber cement to form a sub-assembly.

To calibrate the test apparatus, tests were made on six 6-inch disc specimens of thermal conductance from 0.3 to 4.4 mw/cm²C, each in combination with the dummy specimen of thermal conductance of approximately 0.14 mw/cm²C, and the steady-state value of V/V_0 was observed in each case. The conductances of the six principal specimens, and of the dummy specimen, were determined by means of previous tests conducted on them in the form of 2-inch squares in the Bureau's guarded hot plate apparatus (ASTM Designation C177-45).

The results of the calibration measurements are recorded in Table 1, and there are plotted in Figure 2 the hot plate values of conductance, k/L, of the principal specimens, versus the observed values of V/V_0 from the conductive disc measurements on them. A regular curve is faired amongst the six calibration points, to yield a smooth curve representing the calibration of the conductive disc apparatus. Departures of the experimental points and the curve do not exceed one percent.

The conductances in Figure 2 are values corresponding to the mean temperature of the specimen in the conductive disc test when the cold plate temperature was about 3°C and the disc mean temperature was about 6°C. In tests made with the conductive disc apparatus, using the calibration curve of Figure 2, the conductance obtained requires correction, as indicated below, to compensate for the change in disc conductivity if the disc mean temperature departed significantly from 6°C. The corrected conductance corresponds to the actual mean temperature of the specimen in the conductive disc test.

The temperature coefficient of conductivity of type 347 stainless steel (in the equation $k_t = k_0(1 + (t_d - 6))$) is 0.001, approximately. Accordingly, the conductance obtained from the calibration curve, k/L(c.c.), should be corrected by the relation

$$\frac{k}{L}(\text{at } t_d) = \frac{k}{L}(\text{c.c.}) \times [1 + 0.001(t_d - 6)] \qquad (8)$$

Taking the value of k/L (2.31 mw/cm²C) from the calibration curve at V/V₀=1.15, and the value of k'/L'=0.137 at 40°C mean temperature, and using Equations (4) and (2a), the conductivity of the Type 303 stainless steel of the disk is calculated to be 0.159 w/cm C at 49°C. A measurement made here in 1956 on a sample of Type 303 rod 1 inch in diameter indicated its conductivity to be 0.141 w/cm C at 69°C. NBS Circular 559, "Thermal Conductivity of Metals and Alloys at Low Temperatures, a Review of the Literature" (1954), gives data (Figure 2) which indicate that the conductivity of U.S. 303 at 69°C is about 0.153; the Stainless Steel Handbook of the Allegheny Steel Corporation indicates a value of 0.155 w/cm C at 69°C. The value of disc conductivity obtained from the disc calibration measurements is seen to be intermediate between available values from other measurements.

5. PROCEDURE AND RESULTS

In the present use of the apparatus, the lower cold plate, the dummy specimen, and the conductive disc formed a sub-assembly, and it was necessary only to interpose the single test specimen between the conductive disc and the upper cold plate. For good thermal contact, the test specimen must be flat and of uniform thickness, and the contacting surfaces must be clean. To improve thermal contact between the working surfaces and the specimen, an 18-lb weight was centered on the upper cold plate, resulting in a pressure on the specimen of approximately 0.8 psi. Care was taken to assure that the several circular parts and the weight were positioned coaxially.

Ball bearings are set near the edges in the outward faces of both cold plates at angular spacings of 120°. Micrometer measurements of the axial distance across the ball bearings in the two cold plates, with and without the test specimen in place, enabled the thickness of the specimen to be accurately determined.

Thermal insulation of the working parts of the assembled apparatus was accomplished by pouring around it within a removable 12-inch diameter container a free-flowing powder insulation (silica aerogel). The powder insulation was readily drained from around the apparatus by opening a sliding gate at the bottom of the container.

To start a test, the disc heater winding was energized at a reasonable power input rate (an initial setting of about 6 watts input was used for these measurements), and if the power input and the cooling water temperature were constant, the apparatus reached a substantially steady temperature condition in from 2 to 3 hours. Readings of V and V_c were then made periodically for an hour or more to assure that steady-state conditions existed. The value of the ratio V/V_c does not depend on the rate of power input, but to determine this ratio with good precision. It is desirable that the difference between V and V_c be determinable with a precision of better than 1 part in 200, and therefore that the rate of power input be adjusted to yield an adequate difference of V and V_c. In testing explosives, however, it was desirable that the maximum temperature of the disc in contact with the test specimen be limited to some safe value. For this apparatus the maximum disc temperature, which occurs at the rim, is approximately equal to

$$t_{max} = t_c + V_c(V/V_c)^2 \qquad (9)$$

for values of V/V_c up to 1.3.

6. RESULTS OF MEASUREMENTS ON EXPLOSIVES

Table 2 summarizes the data obtained with the conductive disc apparatus on explosives.

The six materials were found to have thermal conductivities between 1.9 and 2.6 mw/cm C.

During the course of the measurements made in the underground vault on the explosives, two check measurements were made on the original 1.28-cm Neoprene specimen used in calibrating the apparatus. The first was made on initially setting up the apparatus in the vault prior to the first TNT measurement. Following the second TNT measurement, it was necessary to clear the vault for other work, and the second check test was made when the apparatus was reinstalled, just prior to the measurement of the Pentolite specimen. The conductance of the Neoprene specimen, as determined by the hot plate and used in the calibration test, was 2.44 mw/cm² C at 46°C mean temperature. In the first check test, the conductance obtained was 2.50 at 45°C; in the second, 2.52 at 40°C. There was therefore an observed variation in results of 3.4 percent, to which the results on the explosives must be considered subject.

The two measurements made on ITT, at 33 and 38°C, indicate a negative temperature coefficient of conductivity (α = -0.011 per deg C). Because of the small difference in test temperatures, the uncertainty in this value of α is probably large. Hot plate tests conducted on paraffin (133°F M.P.) and Halowax at 70° to 77°F mean temperature have indicated temperature coefficients of -0.003 and -0.0041 per deg C, respectively, for these waxy materials.

TABLE 1 - CALIBRATION MEASUREMENTS

Principal Specimen	Hot Plate Data k/L* kw/cm² °C	Heater Volts	V/V₀	Conductive Disc Data Cold Plate Temp. t_c °C	Mean Temp. at r=0 t_{hi} °C	Mean Temp. at r=r₁** t_{hi} °C	Rim °C	Mean Temp.(corr.) Disc °C	Mean Temp.(corr.) Specimen °C
Fiber glass board 1.11 cm	0.3093	29	1.0273	26.22	66.89	67.99	69	67.4	46.6
Gum rubber 1.19 cm	1.342	30	1.0996	26.76	64.36	67.75	72	66.0	46.4
Neoprene 91.7 pcf 1.22 cm	2.494	40	1.1614	26.29	66.27	72.73	82	69.5	47.1
Neoprene 94.0 pcf 1.32 cm	2.944	43	1.1836	23.49	65.55	72.72	83	69.1	46.8
Neoprene 97.3 pcf 1.32 cm	3.117	45	1.1970	26.73	63.41	73.73	84	69.2	46.0
Gum rubber 0.36 cm	4.375	55	1.2704	26.13	66.59	77.53	93	72.0	45.0

* k/L is corrected to correspond to the mean temperature of the specimen in the conductive-disc test. The conductance of the dummy specimen, k'/L', was 0.116 $(1+3.00)(t_m)$ kw/cm² °C, where t_m is its mean temperature.

** Average of three temperatures at r=5.08cm, at 120° angular spacing.

TABLE 2 - THERMAL CONDUCTIVITY, k, OF EXPLOSIVES

Specimen	Thickness (cm)	X/Xc	Cold Plate Temp. (°C)	Hot Plate Center Temp. (°C)	Hot Plate Ave. Temp. at R=5.08cm (°C)	Mean Room Temp. (°C)	Specimen Mean Temp. (°C)	Specimen k max. cal/cm sec °C
[illegible]	1.272	1.1054	34.72	40.18	41.87	41	11	2.04
[illegible]	1.272	1.1053	24.97	30.34	33.01	32	28	1.63
[illegible]	1.272	1.1316	18.87	44.25	47.21	46	32	2.59
[illegible]	1.272	1.1358	8.74	18.17	19.73	19	13	2.51
[illegible]	1.270	1.1275	8.65	12.00	13.52	13	6	2.53
[illegible]	1.261	1.1063	21.47	51.19	54.35	53	39	2.05
[illegible]	1.273	1.1354	23.24	47.17	50.43	49	36	2.57

U.S. DEPARTMENT OF COMMERCE
Frederick H. Mueller, Secretary
NATIONAL BUREAU OF STANDARDS
A. V. Astin, *Director*

THE NATIONAL BUREAU OF STANDARDS

The scope of activities of the National Bureau of Standards at its headquarters in Washington, D.C., and its major laboratories in Boulder, Colorado, is suggested in the following listing of the divisions and sections engaged in technical work. In general, each section carries out specialized research, development, and engineering in the field indicated by its title. A brief description of the activities, and of the resultant publications, appears on the inside of the front cover.

WASHINGTON, D.C.

Electricity and Electronics. Resistance and Reactance. Electron Devices. Electrical Instruments. Magnetic Measurements. Dielectrics. Engineering Electronics. Electronic Instrumentation. Electrochemistry.

Optics and Metrology. Photometry and Colorimetry. Optical Instruments. Photographic Technology. Length. Engineering Metrology.

Heat. Temperature Physics. Thermodynamics. Cryogenic Physics. Rheology. Engine Fuels. Free Radicals Research.

Atomic and Radiation Physics. Spectroscopy. Radiometry. Mass Spectrometry. Solid State Physics. Electron Physics. Atomic Physics. Neutron Physics. Radiation Theory. Radioactivity. X-rays. High Energy Radiation. Nucleonic Instrumentation. Radiological Equipment.

Chemistry. Organic Coatings. Surface Chemistry. Organic Chemistry. Analytical Chemistry. Inorganic Chemistry. Electrodeposition. Molecular Structure and Properties of Gases. Physical Chemistry. Thermochemistry. Spectrochemistry. Pure Substances.

Mechanics. Sound., Mechanical Instruments. Fluid Mechanics. Engineering Mechanics. Mass and Scale. Capacity, Density, and Fluid Meters. Combustion Controls.

Organic and Fibrous Materials. Rubber. Textiles. Paper. Leather. Testing and Specifications. Polymer Structure. Plastics. Dental Research.

Metallurgy. Thermal Metallurgy. Chemical Metallurgy. Mechanical Metallurgy. Corrosion. Metal Physics.

Mineral Products. Engineering Ceramics. Glass. Refractories. Enameled Metals. Concreting Materials. Constitution and Microstructure.

Building Technology. Structural Engineering. Fire Protection. Air Conditioning, Heating, and Refrigeration. Floor, Roof, and Wall Coverings. Codes and Safety Standards. Heat Transfer.

Applied Mathematics. Numerical Analysis. Computation. Statistical Engineering. Mathematical Physics.

Data Processing Systems. SEAC Engineering Group. Components and Techniques. Digital Circuitry. Digital Systems. Analog Systems. Application Engineering.

• Office of Basic Instrumentation.

• Office of Weights and Measures.

BOULDER, COLORADO

Cryogenic Engineering. Cryogenic Equipment. Cryogenic Processes. Properties of Materials. Gas Liquefaction.

Radio Propagation Physics. Upper Atmosphere Research. Ionospheric Research. Regular Propagation Services. Sun-Earth Relationships. VHF Research. Radio Warning Services. Airglow and Aurora. Radio Astronomy and Arctic Propagation.

Radio Propagation Engineering. Data Reduction Instrumentation. Modulation Systems. Radio Noise. Tropospheric Measurements. Tropospheric Analysis. Radio Systems Application Engineering. Radio Meteorology. Lower Atmosphere Physics.

Radio Standards. High Frequency Electrical Standards. Radio Broadcast Service. High Frequency Impedance Standards. Electronic Calibration Center. Microwave Physics. Microwave Circuit Standards.

Radio Communication and Systems. Low Frequency and Very Low Frequency Research. High Frequency and Very High Frequency Research. Ultra High Frequency and Super High Frequency Research. Modulation Research. Antenna Research. Navigation Systems. Systems Analysis. Field Operations.

NBS

Pendaflex
FROM TO DO... TO DONE
Pendaflex
FROM TO DO... TO DONE
Pendaflex
FROM TO DO... TO DONE
Pendaflex
Esselte
48434
30%
Pendaflex
FROM TO DO... TO DONE
P4